



Chairperson: Gert Gouws – 078 699 9318
Secretary: Renette Lategan — 078 252 4076
FPO: Gerrie Visagie – 078 350 9256
E-mail: tfa@webmail.co.za
Registration nr:1572/01

TFPA VISION:

To make every owner on whose land a veldfire may start or burn or from whose land it may spread, aware of the rules and regulations as pertained in the act: National Veld and Forest fire Act, 2001 as amended.

TFPA minimum requirements and guidelines for Legal Proceedings

As approved on 12 April 2017

Definition: Plot – Agricultural land 25ha and smaller
Farm – Agricultural land larger than 25ha

TFPA Minimum recommendation regarding fire breaks:

Plots – The fire breaks must have a minimum width of 2m.

Farms - The fire breaks must have a minimum width of 3m.

TFPA Minimum recommendation regarding fire fighting equipment:

Farm	Plot
Bakkie Sakkie	Knapsack
Knapsack	Beaters
Beaters	Rakes
Rakes	
Drip Torch or Fire lighter	
1 Mobile radio per fire fighting team	

TFPA Minimum recommendation regarding PPE:

1. Heat resistant overall or denim overall
2. Cotton T-shirt with long sleeves
3. Firefighting Balaclava, single layer
4. Safety boots – No gumboots or tekkies
5. Leather or denim gloves
6. Heat resistant eye protection
7. Mouth Protection – Dust mask or mutton cloth

TFPA Minimum recommendation regarding Training:

Farm workers: Introduction course to grass and wild land firefighting.

Lodges: The Supervisors should attend at least the Lodge Training course.

TFPA Minimum recommendation regarding fire extinguishers in buildings:

High risk buildings (Thatched roof, sheds, store rooms and farming related buildings):

2 x DCP fire extinguishers per 100²m

Medium risk buildings (Tile or Sink roofed houses):

2 x DCP fire extinguishers per 200²m

The fire extinguishers must be installed at the entrance or exit of the building.

We recommend CO² fire extinguishers and fire blankets to be used in a kitchen.

TFPA recommendation regarding Thatched Roofs:

Thatched roof should have additional water hose reels, hydrant or sprayers protection system (min 2.5bar)

Nozzels must be able to reach all sides of structure and roof (sufficient lengths of hose)

The system must be tested on a regular basis.

Lightning pole - The pole must be earth, maintain and comply with the conditions of your Insurance Company.

TFPA Minimum recommendation regarding clearance around buildings:

Areas around buildings must be kept clean from material that can burn.

Grass must be short and materials with potential to burn (old fuel) be removed.

Trees close to buildings must be trimmed so that fire cannot spread from it to the building.

Areas to be cleaned around buildings:

Lodges - 30m

Farmhouses - 30m

Stores - 30m

Garages - 30m

Worker houses - 20m

Transformer boxes - 10m

Rubbish-dump – 4m graded with no grass visible and it must form part of your existing fire breaks.

Additional control lines should be in place some distance from the clearance. This can be roads, dams, rivers, rocky areas or constructed lines.